



CLEAN STRONG

Cleaning emulsion for removing maintenance product deposits

Description:

Cleaning emulsion for removing contamination from water-resistant flooring.

Especially suitable for surface cleaning of:

- Sealed parquet flooring
- Sealed cork flooring
- Pre-finished parquet
- PVC
- Natural and synthetic stone flooring

Note:

When used on sealed parquet, if left too long to work in, Pallmann CLEAN STRONG can attack the seal-coat. Always conduct a test before proceeding.

Product Properties / Benefits:

Cleaning emulsion that readily removes stubborn soiling and, therefore, is an excellent pre-requisite for the subsequent initial cleaning.

- Ready to use
- Easy to apply
- PH value approx. 10
- Formaldehyde-free

Technical Data:

Packaging: plastic canister/bottle
Packsize: 0.75 litre
Shelf life: approx. 24 months
Colour: transparent
Consumption: 20 – 100 ml/10 l



PALLMANN

CLEAN STRONG

Application:

1. Shake the container well before use.
2. Apply Pallmann CLEAN STRONG according to the degree of contamination.
3. Add approx. 20 – 100 ml to 10 litres of water, and apply evenly with a mop or cloth onto the surface to be cleaned.
4. Leave to work in for approx. 2 – 5 minutes and then brush hard with a stiff broom.
5. Remove the released contamination and rinse twice with clean water. For especially stubborn soiling, repeat if necessary.
6. Regular cleaning maintains the wear life. With Pallmann FINISH CARE, the surface receives optimum protection and the appearance is maintained. Maintenance with Pallmann FINISH CARE should be carried out as required.

Important Notes:

- Shelf life minimum 24 months in original packaging when stored in constant conditions. Protect from frost. Tightly reseal opened containers.
- Optimum conditions are 18 – 25 °C, relative humidity < 65 %. Low temperatures and high humidity lengthen, and high temperatures and low humidity shorten the drying time.
- The cleaned surface should then be maintained with Pallmann FINISH CARE. Regular cleaning with Pallmann FINISH CARE improves the appearance and increases the wear life of the sealed surfaces.

Protection of the Workplace and the Environment

Cleaning emulsion with approx. 5 % of organic solvents. Non-flammable. Requires no special protection or precautions in general use. Avoid contact with skin or contact with eyes. Provide fresh air supply during and after use.

Disposal:

Where possible, collect product residues and re-use. Do not allow into drains, watercourses or landfill. Empty, drip-free plastic or metal containers are recyclable. Containers with liquid residues and liquid waste product are Special Waste. Containers with hardened residues are Construction Waste.

The above information is based on our experience and careful investigations. The variety of associated materials and different construction and working conditions cannot be individually checked or influenced by us. The quality of your work depends, therefore, on your own professional judgement and product usage. If in doubt, conduct a small test or obtain technical advice. Observe the installation recommendations of the covering manufacturer.

The publication of this Product Data Sheet invalidates all previous product information. The respective updated version of this datasheet can be found on our homepage under www.pallmann.net

