



# Clean

## Water-based cleaning fluid for floors

### Suitable for the routine cleaning of the following surfaces:

- Sealed parquet/hardwood floors
- Sealed cork floors
- Oiled and waxed parquet/hardwood floors
- Oiled or sealed engineered boards
- Linoleum
- PVC
- Natural and synthetic stone floors

### Routine cleaning:

Consumption: approx. 100 – 200 ml/10 litres of water

### Suitable for the thorough cleaning of Pallmann oiled /waxed parquet/hardwood floors:

- Oiled and waxed parquet/hardwood floors
- Oiled or sealed engineered boards

### Thorough (deep) cleaning:

Measuring(1): 400 ml/10 litres of water up to undiluted.  
(1) The mixing proportion depends on the level of contamination, from 400 ml/10 litres water, up to undiluted. The exact maintenance routine is shown in the care instructions for the MAGIC OIL 2K range.

### Product Properties /Benefits:

Water-based, neutral, all-purpose cleaner for grime on floors.

- Easy application
- Skin friendly (we always recommend the use of protective gloves)
- pH-neutral

### Technical Data:

Packaging: plastic bottle/canister  
Packsize: 0,75 litres/10 litres  
Shelf life: approx. 24 months, protect against frost  
Color: transparent

### Surface Preparation:

Remove traces of dirt, dust, grease, oil or wax with a mop, broom, or vacuum cleaner.



# Clean

## Routine maintenance:

1. Shake the container well before use.
2. Dilute approx. 100 – 200 ml Pallmann CLEAN with 10 litres of water and apply with a mop or cloth.
3. After the treatment with Pallmann Clean, we recommend maintaining the cleaned surface, depending upon surface treatment with the appropriate product
4. The exact maintenance routine is shown in the care instructions for sealed- and oiled/waxed floors for MAGIC OIL 2K products or SOYABASE PLUS.

## Thorough (deep) cleaning of oiled/waxed parquet/ hardwood floors treated with Magic Oil 2K products or SOYABASE PLUS.

1. Shake the container well before use.
2. Assess the level of contamination and dilute Pallmann CLEAN to the correct rate.
3. Approx. 400 ml/10 litres of water up to undiluted. The surface to be cleaned should only be damp wiped (not wet).
4. Remove the dirt from the surface with a suitable mop, brush or rotary machine (green pad).
5. After cleaning, always damp wipe down the surface with clean water.
6. Clean tools after use with clean water.
7. The thorough cleaned floor requires re-treating with the respective oil-wax system (MAGIC OIL 2K range)
8. The exact maintenance routine is shown in the care instructions for the MAGIC OIL 2K range.

## Important Notes:

- Shelf life minimum 24 months in original packaging when stored in relatively cool conditions. Tightly re-seal opened packaging and use as quickly as possible. Protect against frost.
- On the newly coated flooring do not use any cleaners and/or maintenance products for a minimum of 8 days.
- Newly impregnated floors (with Pallmann SOYABASE PLUS) may be treated at the earliest after 4 days with Pallmann CLEAN.
- Newly impregnated floors (with Pallmann MAGIC OIL 2K) may be treated at the earliest after 12 hours with Pallmann CLEAN.
- Regular maintenance with FINISH CARE improves the visual appearance and increases the wear-life of the sealed surfaces.
- Regular treatment with or Pallmann MAGIC OIL CARE (impregnated wood-floors) improves the appearance and increases the wear life of the hardwood flooring.

## Protection of the Workplace and the Environment:

Non-flammable. Requires no special protection or precautions in general use. Avoid contact with skin or contact with eyes. Provide fresh air supply during and after use.

## Disposal:

Disposal should be in accordance with local, state or national legislation. Where possible, collect product residues and re-use. Do not allow into drains, watercourses or landfill. Empty, drip-free plastic or metal containers are recyclable. Containers with liquid residues and liquid waste product are Special Waste. Containers with hardened residues are Construction Waste.

The above information is based on our experience and careful investigations. The variety of associated materials and different construction and working conditions cannot be individually checked or influenced by us. The quality of your work depends, therefore, on your own professional judgement and product usage. If in doubt, conduct a small test or obtain technical advice. Observe the installation recommendations of the covering manufacturer.

The publication of this Product Data Sheet invalidates all previous product information. The respective updated version of this datasheet can be found on our homepage under [www.pallmann.net](http://www.pallmann.net)

