



FINISH CARE STOP

Care- and cleaning-emulsion especially for slip-resistant flooring

Description:

Water-based wash-care combination for ongoing cleaning and maintenance.

Especially suitable for the surface care of:

- Sealed wood flooring
- Sealed cork flooring
- Sealed pre-finished wood flooring
- Linoleum
- PVC
- Natural and artificial stone flooring

Note:

This product has been specially developed to take into account the particular requirements of DIN 18 032. We recommend this slip-resistant care product for: sports halls, homes for the elderly, kindergartens.

Product Properties / Benefits:

Cleaning emulsion that readily removes stubborn soiling and, therefore, is an excellent pre-requisite for the subsequent initial cleaning.

- Ready to use
- Easy to apply
- PH value approx. 10
- Formaldehyde-free

Technical Data:

| | |
|--------------|--------------------------|
| Packaging: | plastic bottle |
| Packsizes: | 0.75 litre |
| Shelf life: | approx. 24 months |
| Colour: | transparent |
| Consumption: | approx. 20 – 100 ml/10 l |



PALLMANN

FINISH CARE STOP

Application:

1. Before use, shake the container well.
2. Initial Care: Apply a thin, even coat of Pallmann FINISH CARE STOP using approx. 10 ml undiluted and applied with a fine, damp sponge. Polishing is not necessary. After 60 minutes, the surface can be used.
3. Initial maintenance: After approx. 1 day the initial maintenance can be carried out with Pallmann FINISH CARE STOP. Dilute approx. 50 – 100 ml with 10 litres of water and apply thinly with a sponge, cloth or mop. After 60 minutes, the surface can be used. This maintenance should be carried out as required.
4. On deep cleaned floors (Pallmann CLEAN STRONG) we recommend a initial coating with Pallmann FINISH CARE STOP. The care and cleaning frequency is available in the upkeep instruction for sealed wooden floors.

Protection of the Workplace and the Environment:

Solvent-free and non-flammable, and requires no special protection or precautions in general use.
Avoid prolonged contact with skin, or contact with eyes.

Disposal:

Where possible, collect product residues and re-use. Do not allow into drains, watercourses or landfill. Empty, drip-free plastic or metal containers are recyclable. Containers with liquid residues and liquid waste product are Special Waste. Containers with hardened residues are Construction Waste.

The above information is based on our experience and careful investigations. The variety of associated materials and different construction and working conditions cannot be individually checked or influenced by us. The quality of your work depends, therefore, on your own professional judgement and product usage. If in doubt, conduct a small test or obtain technical advice. Observe the installation recommendations of the covering manufacturer.

The publication of this Product Data Sheet invalidates all previous product information. The respective updated version of this datasheet can be found on our homepage under www.pallmann.net

Important Notes:

- Shelf life minimum 24 months in original packaging when stored in constant conditions. Protect from frost. Tightly reseal opened containers.
- Optimum conditions are 18 to 25 °C and relative humidity < 65 %. Low temperatures and high humidity lengthen, and high temperatures and low humidity shorten the drying time.
- Leave freshly sealed surfaces at least one day before covering with carpeting or other floor coverings, or loading with heavy objects.
- Regular maintenance with Pallmann FINISH CARE STOP improves the appearance and increases the life expectancy of the sealed surface.

