



HYDRO FILLER

Water-based joint filler for wood flooring

Description:

Water-based joint filler for filling joints in wood flooring.

Suitable for joint filling of:

- Sanded parquet, solid wood flooring
- Suitable for use on underfloor heating systems

Product Properties / Benefits:

Water-based joint filler with good viscosity to avoid joint failure.

- Ready to use
- Easy to apply
- Rapid drying
- Excellent filling capacity
- Suitable for all standard timbers
- Does not clog sanding materials

Technical Data:

Packaging:	plastic container
Packsize:	5 litre
Shelf life:	min. 12 months
Colour:	white
Consumption per coat:	approx. 50 – 100 g dependent on floor condition
Working temperature:	18 – 25 °C
Ready for sanding:	after 20 – 30 minutes *

*Under normal climatic conditions.



HYDRO FILLER

Surface Preparation:

After the adhesive is fully hardened, the surface treatment can commence. The surface must be free from dirt, oil, wax and silicone. Prepare the surface with a drum-sanding machine with Pallmann ABRASIVE GRADE 36 to 60 grit.

Application:

1. Before use, allow the containers to come to room temperature and shake well.
2. On the surface, mix HYDRO KITT with fine sanding dust of the type of wood to be sealed and blend to a paste that can be trowel applied.
3. Using the stainless steel Pallmann Surface Trowel, fully cover the whole floor.
4. After approx. 20 – 30 minutes drying time, the sealed surface is ready for sanding
5. Sand the surface well using Pallmann Sandpaper grade 100 on a drum-sander. To remove the sanding marks from the drumsander, it is advisable to finish off using a rotary sanding machine with a Sanding grit 120.
6. Clean tools with water.

Important Notes:

- Shelf life minimum 12 months in original packaging when stored in relatively cool conditions. Protect from frost. Tightly reseal opened containers and use the contents as quickly as possible.
- Optimum conditions are 18 to 25 °C and relative humidity >35% and < 65%. Low temperatures and high humidity lengthen, and high temperatures and low humidity shorten the drying time.
- Suitable for joints up to 2 mm.
- For dark, exotic timbers, we recommend you test a small section for suitability in advance.
- The following standards and notices are applicable and especially recommended: DIN 18 356 "Working with parquet".

Protection of the Workplace and the Environment:

Water-based seal, solvent content less than 5%. Suitable as a substitute material for high solvent content materials used for parquet surface treatment. During application, the use of barrier cream, as well as ventilation of the work areas, is recommended.

Disposal:

Where possible, collect product residues and re-use. Do not allow into drains, watercourses or landfill. Empty, drip-free plastic or metal containers are recyclable. Containers with liquid residues and liquid waste product are Special Waste. Containers with hardened residues are Construction Waste.

The above information is based on our experience and careful investigations. The variety of associated materials and different construction and working conditions cannot be individually checked or influenced by us. The quality of your work depends, therefore, on your own professional judgement and product usage. If in doubt, conduct a small test or obtain technical advice. Observe the installation recommendations of the covering manufacturer.

The publication of this Product Data Sheet invalidates all previous product information. The respective updated version of this datasheet can be found on our homepage under www.pallmann.net

